



GROUND PRODUCTS – 3000 GALLON
MODEL: 3MA100SCANDAS-DUAL

Cab & Chassis

Meets FED STD 807

Tank

3,000 Gallon two compartment aluminum alloy fully baffled, overturn protection, future vapor recovery ready, manhole with venting, full length under-frame. Tank is DOT406 compliant. Tank is painted one color.

Dual Pumping Systems

Components rated for 100 gallons per minute. Hot shift PTO, pump inlet strainer, positive displacement pump, meter with air eliminator, reset counter and totalizer, pressure gauge, electric rewind hose reel, 1-1/2" x 100' hose, swivel and nozzle. Dispensing equipment mounted on open platform (one each side) of unit.

Loading System

Tank is bottom loading ready which includes; Internal bottom loading valve, Kamlock style dry break adaptor, pressure gauge, manual shut off valve, Jet level sensor and overfill pre check valve. Tank is also capable of being loaded through the man way on top of tank.

Miscellaneous

Brake interlock for PTO and bottom loading operations with brake override capabilities, pumping system operation and parts manual, light at pumping platform and register head, floodlight at cabinet area, weather proof electrical junction box, rear fenders, tank access ladder, tank water drain, schematic and operating plates, 20 lb fire extinguishers, static ground reel with clamp, one emergency shut down control, tank capacity chart with gauge stick, product placards and product decals. Unit meets requirements of NFPA 385

Training

Onsite training at your facility is provided with unit.